



LS Portable branchpipe

- Portable low expansion foam making branchpipe LS type,
(to be used combined with the Z 2 type self-priming inline premixer),
- premix flowrate 200 to 800 lt/min at 5 bar,
 - expansion rate ca. 1÷7,
 - inlet nipple in light alloy EN AB 42000-Al Si 7 MgTA with pressure indicator,
foam pipe light alloy with synthetic support handle,
with bumper ring in rubber on the outlet of the foam pipe,
 - inlet threading G male or coupling,
 - min. range of jet 17 to 32 mt. at nominal flowrate,

Threadings							
Type	Code nr.	Premix flowrate (lt/min)	Expansion rate	Inlet threading	Min. range of jet (mt.)	Weight (Kg)	Dwg. nr.
LS 2	1951101009	200	1÷7	2"	17	0.7	19200202
LS 4	1951301009	400	1÷7	2"	25	0.8	19200202
LS 8	1951601009	800	1÷7	2½"	32	1.4	19200202

with coupling UNI type							
Type	Code nr.	Premix flowrate (lt/min)	Expansion rate	Coupling type	Min. range of jet (mt.)	Weight (Kg)	Dwg. nr.
LS 2	1951101020	200	1÷7	45	17	1.3	19200202
LS 4	1951301020	400	1÷7	45	25	1.4	19200202
LS 8	1951601030	800	1÷7	70	32	2.6	19200202

with coupling STORZ type							
Type	Code nr.	Premix flowrate (lt/min)	Expansion rate	Coupling type	Min. range of jet (mt.)	Weight (Kg)	Dwg. nr.
LS 2	1951103220	200	1÷7	C52	17	0.9	19200202
LS 4	1951303220	400	1÷7	C52	25	1.0	19200202
LS 8	1951603330	800	1÷7	B75	32	1.8	19200202

Caccialanza & C. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.