



## M Portable branchpipe

Portable medium expansion foam making branchpipe M type,

(to be used combined with the Z 2 type self-priming inline premixer),

- premix flowrate 200 to 800 lt/min at 2,5 bar,
- expansion rate ca. 1÷75 (1÷50 for M8 type),
- foam flowrate 15 to 40 m<sup>3</sup>/min. with 3% synthetic and AFFF foam compound,
- inlet nipple with support ring and outlet support ring in light alloy EN AB 42000-Al Si 7 MgTA,  
body stainless steel plate AISI 304 with synthetic support handle,  
internal sieve stainless steel AISI 304,  
spray nozzle brass,
- inlet threading G male or coupling,
- min. range of jet 8 to 12 mt. at nominal flowrate,

Threading G male							
Type	Code nr.	Premix flowrate (lt/min)	Foam flowrate (m <sup>3</sup> /min)	Inlet threading	Minimum range (mt)	Weight (Kg)	Dwg. nr.
M 2	1953102009	200	15	2"	8	3.0	19400001
M 4	1953302009	400	30	2"	10	4.5	19400001
M 8	1953602009	800	40	2½"	12	5.7	19400001

with coupling UNI type							
Type	Code nr.	Premix flowrate (lt/min)	Foam flowrate (m <sup>3</sup> /min)	Coupling type	Minimum range (mt)	Weight (Kg)	Dwg. nr.
M 2	1953102020	200	15	45	8	3.6	19400001
M 4	1953302020	400	30	45	10	5.1	19400001
M 8	1953362030	800	40	70	12	6.8	19400001

with coupling STORZ type							
Type	Code nr.	Premix flowrate (lt/min)	Foam flowrate (m <sup>3</sup> /min)	Coupling type	Minimum range (mt)	Weight (Kg)	Dwg. nr.
M 2	1953103200	200	15	C52	8	3.3	19400001
M 4	1953303200	400	30	C52	10	4.8	19400001
M 8	1953603300	800	40	B75	12	6.1	19400001