



A4-DA Monitors

Twin agent for powder and foam compound

A4 Monitors LL (Light Alloy EN AB 42000-Al Si 7 MgTA)

A4/DA/F/P, LL, twin agent with foam/water pipe and powder pipe

A4 Monitors Bz (Bronze B ZN 7)

- A4/DA/F/P, LL, twin agent with foam/water pipe and powder pipe

Caccialanza & C. reserves the right to change or modify without previous notice any data or specification due to changes or modification in order to improve the products presented.



A4/DA/LL twin agent with foam pipe and powder pipe

- Handlever operated double pipe foam/water monitor A4/DA type,
- body seawater resistant light alloy EN AB 42000-Al Si 7 MgTA,
 - handlever operation with locking devices for arresting the horizontal and the vertical movements in all positions,
 - horizontal and vertical movements on self-lubricating Lubrifon slide bearings and teflon rings with greasing nipples, rotation 360°, elevation +70°/-60°,
 - inlet flange 4" ANSI 150 lbs R.F., or DN 100 DIN PN 16 alternatively inlet flange 6" ANSI 150 lbs R.F., or DN 150 DIN PN 16
 - with double outlet for foam pipe and dry chemical pipe,
 - with foam pipe A type, nozzle light alloy EN AB 42000-Al Si 7 MgTA, pipe stainless steel AISI 304,
 - with dry chemical pipe, nozzle light alloy EN AB 42000-Al Si 7 MgTA, pipe stainless steel AISI 304,
 - external protective painting: sandblasting SA 2,5, n.1 epoxy primer coat d.f.t. ≥40μ, n.2 final polyurethanic coat red RAL 3000, d.f.t. ≥30μ each, total d.f.t. ≥100μ

4" ANSI 150 lbs R.F. flange							
Type	Code nr.	Flowrate at 8 bar (lt./min.)	Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274126820	2.000(F)	40(P)	8,3 12	54(F) 40(P)	59	52859906
DN 100 DIN PN 16							
Type	Code nr.	Flowrate at 8 bar (lt./min.)	Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274121820	2.000(F)	40(P)	8,3 12	54(F) 40(P)	59	52859906

(P)= powder pipe (F)= foam pipe

* Minimum warranted range of jet at nominal pressure.



6" ANSI 150 lbs R.F. flange						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274127820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	63	52859906
DN 150 DIN PN 16						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4 /DA	5274122820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	63	52859906

(P)= powder pipe (F)= foam pipe

* Minimum warranted range of jet at nominal pressure.



A4/DA/Bz twin agent with foam pipe and powder pipe

Handlever operated double pipe foam/water monitor A4/Da type,

- body Bronze B ZN 7 for seawater service,
- handlever operation with locking devices for arresting the horizontal and the vertical movements in all positions,
- horizontal and vertical movements on self-lubricating Lubrifon slide bearings and teflon rings with greasing nipples, rotation 360°, elevation +70°/-60°,
- inlet flange 4" ANSI 150 lbs R.F., or DN 100 DIN PN 16 alternatively inlet flange 6" ANSI 150 lbs R.F., or DN 150 DIN PN 16
- with double outlet for foam pipe and dry chemical pipe,
- with foam pipe A type, nozzle Bronze B ZN 7, pipe stainless steel AISI 304,
- with dry chemical pipe, nozzle Bronze B ZN 7, pipe stainless steel AISI 304,
- external protective painting: sandblasting SA 2,5, n.1 epoxy primer coat d.f.t. ≥40μ, n.2 final polyurethanic coat red RAL 3000, d.f.t. ≥30μ each, total d.f.t. ≥100μ

4" ANSI 150 lbs R.F. flange						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274226820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	114	52859906
DN 100 DIN PN 16						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274221820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	114	52859906

(P)= powder pipe (F)= foam pipe

* Minimum warranted range of jet at nominal pressure.



6" ANSI 150 lbs R.F. flange						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4/DA	5274227820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	118	52859906
DN 150 DIN PN 16						
Type	Code nr.	Flowrate at 8 bar (lt./min.) Discharge rate (kg/sec)	Pressure at inlet flange (bar)	Range of jet (mt.) *	Weight (Kg)	Dwg. nr.
A4 /DA	5274222820	2.000(F) 40(P)	8,3 12	54(F) 40(P)	118	52859906

(P)= powder pipe (F)= foam pipe

* Minimum warranted range of jet at nominal pressure.